

FRANKLIN INTL -- 2213 FRANKLIN TITEBOND WOOD GLUE
MATERIAL SAFETY DATA SHEET
NSN: 804000F052495
Manufacturer's CAGE: 25589
Part No. Indicator: A
Part Number/Trade Name: 2213 FRANKLIN TITEBOND WOOD GLUE

=====
General Information
=====

Company's Name: FRANKLIN INTL INC
Company's Street: 2020 BRUCK ST
Company's City: COLUMBUS
Company's State: OH
Company's Country: US
Company's Zip Code: 43207-2329
Company's Emerg Ph #: 614-443-0241AM/614-445-1411PM
Company's Info Ph #: 800-347-4583/614-443-0241
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 001
Status: SE
Date MSDS Prepared: 01JAN91
Safety Data Review Date: 28JAN97
Preparer's Company: FRANKLIN INTL INC
Preparer's St Or P. O. Box: 2020 BRUCK ST
Preparer's City: COLUMBUS
Preparer's State: OH
Preparer's Zip Code: 43207-2329
MSDS Serial Number: CDBSJ

=====
Ingredients/Identity Information
=====

Proprietary: NO
Ingredient: VINYL ACETATE
Ingredient Sequence Number: 01
Percent: <0.4
NIOSH (RTECS) Number: AK0875000
CAS Number: 108-05-4
OSHA PEL: 10 PPM
ACGIH TLV: 10 PPM
Other Recommended Limit: 10 PPM

Proprietary: NO
Ingredient: VOLATILE ORGANIC CONTENT: LESS WATER = 10.7 G/L MAXIMUM
Ingredient Sequence Number: 02
NIOSH (RTECS) Number: 9999999VO

=====
Physical/Chemical Characteristics
=====

Appearance And Odor: LIGHT YELLOW OPAQUE LIQUID W/FAINT CHARACTERISTIC
ODOR
Boiling Point: 212F
Vapor Density (Air=1): <1
Specific Gravity: 1.09
Evaporation Rate And Ref: (WATER = 1): 1
Solubility In Water: MISCIBLE

Percent Volatiles By Volume: 54/WT
pH: 4.5

=====
Fire and Explosion Hazard Data
=====

Flash Point: NONE
Extinguishing Media: WATER
Special Fire Fighting Proc: WEAR MESA/NIOSH APPROVED SCBA.
=====

Reactivity Data
=====

Stability: YES
Cond To Avoid (Stability): FREEZING.
Materials To Avoid: STRONG BASES & STRONG ACIDS.
Hazardous Decomp Products: WHEN BURNED: OXIDES OF CARBON & MONOMER.
Hazardous Poly Occur: NO
Conditions To Avoid (Poly): MULTIPLE CYCLES OF FREEZING & THAWING.
=====

Health Hazard Data
=====

Route Of Entry - Inhalation: NO
Route Of Entry - Skin: NO
Route Of Entry - Ingestion: NO
Health Haz Acute And Chronic: SKIN/EYES: IRRITATION.
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: NO
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: NONE
Signs/Symptoms Of Overexp: DIZZINESS, RASH, IRRITATION.
REMOVE TO FRESH AIR. EYES: RINSE W/RUNNING WATER FOR 15 MINS. SKIN: WASH
W/SOAP & WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.
=====

Precautions for Safe Handling and Use
=====

Steps If Matl Released/Spill: IF PRODUCT HAS DRIED, SCRAPE UP & PLACE IN
APPROVED CONTAINER FOR DISPOSAL.
Waste Disposal Method: DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.
Precautions-Handling/Storing: KEEP FROM FREEZING.
Other Precautions: KEEP OUT OF REACH OF CHILDREN.
=====

Control Measures
=====

Respiratory Protection: WEAR SUITABLE NIOSH/MSHA APPROVED RESPIRATOR WHERE
AIRBORNE LIMITS ARE EXCEEDED, 10 PPM FOR VINYL ACETATE MONOMER.
Ventilation: LOCAL EXHAUST: AT POINT WHERE PRODUCT IS DRIED/STANDARD
PLANT.
Protective Gloves: IMPERVIOUS
Eye Protection: SPLASHPROOF SAFETY GOGGLES
=====

Transportation Data
=====

Disposal Data
=====

Label Data
=====